


ECG200+

The full format 12 lead Electrocardiograph for your Hospital



- Effective and powerful 12 lead diagnostic Electrocardiograph, optimizes Hospital ECG workflow thanks to a smart user interface and seamless data integration.
- Quick ECG acquisition for fast and easy operation.
 Highly accurate measurements exceeding the most stringent standards and international recommendations.
- ECG formats: SCP, PDF-GDT-XML. DICOM (internally generated) and HL7 are optional.

- Maximum networking through LAN, Wi-Fi (optional) connectivity and USB port, ensuring seamless plug and play communication. Direct patient demographic data import and ECG export to dedicated ECG management systems, HIS or PACS.
- Thanks to the flat silicone keyboard, the entire surface of the device is now easy to clean and disinfect.
- Glasgow ECG Interpretation Option for adult and pediatric patients, STEMI
- Optional GDPR module, allows complete protection of sensitive data stored on the electrocardiograph by strong authentication installed on the device.
- Dedicated Hospital grade cart

rev01 25/11/2021 www.cardioline.com

Technical specifications

ECG channels

Patient cable

CMRR

Input impedance

Sampling rate of the input stage

Output data resolution

Dynamic range

Bandwidth

Pacemaker detection

Filters

Defibrillation protection

Front-end performance

Lead configuration

Acquisition mode

Lead fail detection

Storage

ECG interpretation

Export

Battery

12-Lead (I, II, III, aVR-L-F, V1-6)

Standard 15D, 10 wires

> 100dB

> 100MΩ

24 bit, 32000 samples/second/channel

1μV/LSB - 1000 samples/second/channel

+/- 400 mV

Performances equivalent to 0,05-300 Hz

Hardware detection coupled with convolution digital filtering

Linear phase digital diagnostic high-pass filter (acc. to 60601-2-25 2nd ed.)50/60 Hz AC

interference adaptive digital filter

Digital low pass filters at 25/40/150 Hz, for display and printing only

AAMI/IEC standards

ANSI/AAMI IEC 60601-2-25:2011

Standard or Cabrera

Automatic (12 leads), Manual (3/6/12 leads), Stat (12 leads)

Independent on all leads

Internal storage up to 100 ECGs (Extended memory option to 1000 ECGs)

Glasgow Analysis Program for Adult, Pediatric, STEMI

SCP-PDF Standard format • XML-GDT Included in standard connectivity option

DICOM Included in DICOM connectivity option • HL7 optional

Battery type: NiMh; Battery duration: more than 500 ECGs and more than 5 hours



Optional GDPR module, allows complete protection of sensitive data stored on the electrocardiograph by strong authentication on the device.

Maximum networking through LAN, optional Wi-Fi connectivity and USB port, ensuring seamless plug and play communication. Direct patient demographic data import and ECG export to dedicated management systems, HIS or PACS.

